



Electrical Information		
<b>Model No.</b>	ST14-040	ST14-060
<b>Power Consumption(±5%)</b>	40W	60W
<b>Power Supply</b>	Sosen	
<b>Input Voltage</b>	100-277 VAC, 277-480 VAC	
<b>Power Factor</b>	≥0.9	
<b>Surge Protection</b>	6kV line-line, 10kV line-earth	
<b>Driver Type</b>	Constant Current (CC)	
<b>Control</b>	1-10V Dimmable Microwave Sensor, PIR Sensor, Emergency	

Optic Information		
<b>LED Type</b>	LED 3030	
<b>Luminous Flux (±10%)</b>	5600LM	8400LM
<b>Efficacy(5000K Ra70)</b>	140lm/W	
<b>Correlated Color Temperature</b>	5000K (4000K optional)	
<b>Color Rendering Index</b>	Ra70	
<b>Beam Angle</b>	R08801	
<b>UGR level</b>	NA	

## Description

Garage light is low-profile, durable and state-of-the-art fixture. It is designed for indoor parking garage which can quickly and easily upgrade existing H.I.D. and fluorescent fixtures.

## Key Features

- Brightest Parking Garage Light in the Market: up to 140lm/W
- Multiple Mounting: Ceiling Mounting/Pipe Mounting
- Built-in Motion Sensor to save more energy
- Easy Installation & Maintenance

## Applications

- Indoor Parking Garages
- Service Corridor
- Fire Stairs

## Dimensions and Mount


<b>Product Dimension</b>	282×252×89mm (11.1"×9.92"×3.5")	
<b>Luminaire Net Weight</b>	2.3±0.3kg(5.07±0.66Lbs)	2.5±0.3kg(5.51±0.66Lbs)
<b>Export Carton Size</b>	680×327×319mm(26.77"×12.87"×12.56")	
<b>Gross Weight</b>	2.7 ± 0.3kg(5.94 ± 0.66Lbs)	
<b>Mounting Option</b>	Ceiling mounting , Pipe mounting	
<b>Material</b>	Aluminum Alloy Polycarbonate Optical Lens	
<b>Finish</b>	Powder Coating	
<b>Fixture Color</b>	Bronze	
<b>EPA</b>	NA	
<b>IK Rating</b>	IK08	
<b>IP Rating</b>	IP66	

## Lifespan and Warranty

<b>Operating Temperature</b>	-30°C to + 50°C(-22°F to 122°F)	
	67,00hrs-L90	
<b>Life Time of LED @Ta=25°C</b>	146,000hrs-L80	
	236,000hrs-L70	
<b>Warranty</b>	5 Years	

## New Features

*\* Please consult us for details.*



R08801

Mounting Options






Ceiling mounting



Pipe mounting

Dimensions



Accessories



**PIR sensor**  
120-277Vac input, IP65 rating,  
max detect height is 15m.



**Microwave motion sensor**  
120-277Vac input, IP65 rating,  
max detect height is 15m.

**Remote control**



**Emergency Kit**  
8W 3H emergency battery kit



**Frosted PC cover**